Copper Cabling Solutions

Category 6A FTP LJ6C Module

The Connectix LJ6C Compact Module range is designed to provide one of the shallowest outlets on the market. They are the ideal solution wherever back box depth is a problem. LJ6C Modules are ideal for use in floor boxes, or any application that has an industry standard LJ6C aperture.

Single and dual gang faceplates are available for up to four LJ6C modules in addition to panels suitable for Ackerman Floor boxes. Their attractive high gloss finish and easy to use labelling system makes them popular with both installers and users alike.

Installation is made easy with individual colour codes and the use of industry standard IDCs. Connectix LJ6C Modules offer extended PowerSum characteristics and exceed the ANSI/TIA-568-C & C.2 specifications. When combined with Connectix Patch Panels and Cable, the link will perform well more than the stated Specification.


ANSI/TIA-568-C.2

Features & Benefits

- Shallow design requires minimal back-box depth
- Industry standard LJ6C size
- Industry standard IDCs
- Individually QA tested
- Interchangeable with other LJ6C modules and blanks
- 25 Year System Warranty Available

Product Specifications		
Width	25mm	
Depth	22mm	
Height	38.5mm	
Back-box depth	32mm	
Mounting Hole	22.3mm x 36.7mm	
Panel Thickness	2.0mm Max	
Material	Flame retardant polycarbonate/ABS thermoplastic resin	
Finish	High gloss	
IDC Labels	Colour coded to T568B	
Sockets	Shielded RJ45	
IDC Blocks	4-way industry standard IDC blocks	





Ordering Information		
Product Description	Part Number	
Cat 6A FTP LJ6C Module	008-000-002-30	



Conforms to