

Copper Cabling Solutions

Category 6 U/UTP B2ca Solid Cable

Category 6 Unshielded Twisted Pair Cable is designed for use in next generation data communications networks, and will comfortably support present applications including Gigabit Ethernet. The B2ca LSZH sheath offers excellent fire performance making this the ideal choice in public buildings and other high risk locations. Connectix Category 6 UTP Solid Cable offers the performance characteristics required by the ever-present Category 6 Standard. Exceeds the requirements of BS6701:2016+A1:2017 for installation cables.

Features & Benefits

- Suitable for Gigabit Ethernet applications
- Supplied metre marked for easy installation
- Excellent performance exceeding ANSI/TIA Enhanced Category 6 specifications
- 305m supplied in an easy pull boxes
- In line with BS6701:2016+A1:2017 specifications
- 25 Year System Warranty Available

Electrical Specifications		
DC Resistance Unbalance	Max 2.5%	
Insulation Resistance	>5000M Ω km	
Capacitance Unbalance (pair to ground)	330 (pF/100m)	
Characteristic Impedance @1-250 MHz	100 +/- 15 Ω	
Velocity Ratio	69%	
Operating Temperature Range	-20°C to +70°C	
Installation Temperature Range	0°C to +50°C	
Dielectric Strength	2500V DC 2s	

Dielectric Strength		2500V DC 2s		
Product Specifications				
Conforms to	1	02.3: 10Base-T, 100Base-T, 1000 Base-T andards; ANSI/TIA 568C; ISO/IEC 11801; RoHS2002/95/ANSI Cenelec EN50174		
Fire Rating		B2ca s1a,d0,a1		
Inner Conductor		0.53mm (+/-0.01mm) plain copper		
Insulation		High density polyethylene		
Construction	4 tv	visted pairs cabled together with spine		
Colour Code		Pair 1: White/Blue-Blue/White Pair 2: White/Orange-Orange/White Pair 3: White/Green-Green/White Pair 4: White/Brown-Brown/White		
Sheath		FR-LSZH		

Orange - 2004

24.5 mm

6.1mm (+/-0.3mm)



Diagram	
 Outer Sheath FR-LSZH Copper Core 	3. Cross Member 4. HDPE Insulation 5. Rip Cord

Ordering Information				
Description	Part Number			
Connectix Cat 6 U/UTP B2ca Orange LSZH Cable - 305m Box	001-003-005-68			



RAL Colour

Overall Diameter

Min. Bending Radius