



## 4000 Series Vertical Outlet

### Features & Benefits

- High density, single gang unit
- Category 6 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available
- Available in a 2 or 4 port version

### Specification

Width	87mm
Depth	27mm
Height	87mm
Material	ABS thermoplastic resin, with grade UL94 VO at 1.5mm flame retardancy
Finish	High gloss
IDC Blocks	Industry standard IDC blocks
PCB	1.6mm double sided PTH boards
Conforms to	TIA/EIA-568-C Category 6 Specification

### Ordering Information

Product Description	Part Number
CCS Cat 6 4 Way Vertical Wall Outlet	008-001-011-10
CCS Cat 6 2 Way Vertical Wall Outlet	008-001-011-20

The Connectix 4000 Series offers Category 6 performance in a high density package.

The 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility.

The position of the sockets on the vertical outlet allows for a compact installation without protruding leads.

