



Features & Benefits

- High density, single gang unit
- Category 6 performance
- No protruding leads
- Designed for direct wall mounting
- Custom logo service available
- Available in a 2 or 4 port version

Specifications

| | |
|-------------|---|
| Width | 87 mm |
| Depth | 27 mm |
| Height | 87 mm |
| Material | ABS thermoplastic resin, with grade UL94 VO at 1.5 mm flame retardancy |
| Finish | High gloss |
| IDC Blocks | Industry standard IDC blocks |
| PCB | 1.6 mm double sided PTH boards |
| Conforms to | TIA/EIA-568-C Category 6 Specification |

Ordering Information

| Product Description | Part Number |
|--------------------------------------|----------------|
| CCS Cat 6 4 Way Vertical Wall Outlet | 008-001-011-10 |
| CCS Cat 6 2 Way Vertical Wall Outlet | 008-001-011-20 |

The Connectix 4000 Series offers Category 6 performance in a high-density package.

The 4000 Series is extremely quick and easy to install; just attach the base plate, snap in the PCB, punch down the cables and install the cover. Gone are the problems of installing modules into a faceplate and pushing excess wires into a back box.

The 4000 Series outlets have been designed for direct wall mounting with top entry mini trunking. In addition, they fit on a standard back box to provide maximum mounting flexibility.

The position of the sockets on the vertical outlet allows for a compact installation without protruding leads.

