



Features & Benefits

- Individually tested up to 250 MHz
- Fully conforms to ANSI/TIA-568-C
- Uses fully shielded cable
- Available from stock in lengths from 0.5 to 5 metres
- Available with blue, red, yellow or green latches
- Offers enhanced security

Specifications

Plug	High performance 50um gold plated
Cable	Category 6 shielded cable
Conforms to	ANSI/TIA-568-C
Boot & Secure Lock	Polycarbonate
Key	Polycarbonate

Ordering Information

Colour	Length	Product Number	Colour	Length	Product Number
Red	0.5 m	003-401-005-05	Blue	0.5 m	003-401-005-03
Red	1 m	003-401-010-05	Blue	1 m	003-401-010-03
Red	2 m	003-401-020-05	Blue	2 m	003-401-020-03
Red	3 m	003-401-030-05	Blue	3 m	003-401-030-03
Red	5 m	005-401-050-05	Blue	5 m	003-401-050-03
Yellow	0.5 m	003-401-005-06	Green	0.5 m	003-401-005-04
Yellow	1 m	003-401-010-06	Green	1 m	003-401-010-04
Yellow	2 m	003-401-020-06	Green	2 m	003-401-020-04
Yellow	3 m	003-401-030-06	Green	3 m	003-401-030-04
Yellow	5 m	003-401-050-06	Green	5 m	003-401-050-04
Boot Removal Key		006-003-007-90			

The Patchlock leads from Connectix provide extra security when installed in public areas as they prevent the risk of unauthorised disconnection of critical network connections. A Removal Key must be used to release the secure lock thus allowing the patch lead to be removed.

The Connectix Category 6 Patch Leads are made from Category 6 stranded cable and are terminated using high performance modular plugs. The fully shielded patch leads increase signal isolation and prevent contaminant noise from entering a cabling system.

Each lead is individually factory tested to the standard to ensure true Category 6 compatibility.

We stock a variety of lead lengths, each available in a number of different colours.

Connectix Category 6 FTP Patch Leads are designed to exceed the performance requirements of the Category 6 Specification.



Boot Removal Key

