Copper Cabling Solutions Compact Module - Category 6 UTP



Category 6 Compact Module is designed to provide one of the shallowest wall outlets on the market. They are the ideal solution wherever back-box depth is a problem.


The attractive high gloss finish and easy to use labelling system are identical to all other Connectix Cabling Systems Modules, making them interchangable in most applications.

Category 6 Compact Modules can be fitted into single or dual gang faceplates and can be combined with quarter blanks and/or voice modules to provide the required configuration.

The modules offer extended PowerSum characteristics and exceed the ANSI/TIA-568-C Category 6 Specification.

Features & Benefits

- Suitable for Gigabit Ethernet applications
- Shallow design requires minimal back-box depth
- Interchangable with other Euro modules and ¼ blanks
- Industry standard IDCs
- Individually QA tested
- Also, available as PABX Secondary or Full Master Voice Module





| Product Specifications | | |
|------------------------|--|--|
| Width | 25mm | |
| Depth | 21mm | |
| Height | 50mm | |
| Back-box depth | Minimum 15mm recommended | |
| Material | Polycarbonate/ABS thermoplastic resin with grade UL94 VO at 1.5mm flame retardancy | |
| Finish | High gloss | |
| IDC Labels | Individual colour coded labels to T568B | |
| Cable Guide | Integrated earth connection / cable tie position | |
| Sockets | Unshielded RJ45 | |
| IDC Blocks | 4-way industry standard IDC blocks | |
| Conforms to | ANSI/TIA-568-C Category 6 Specification | |

| Ordering Information | | |
|-------------------------------|----------------|--|
| Product Description | Part Number | |
| Cat 6 Compact UTP Euro Module | 008-000-001-20 | |

